

Verizon 3.5 GHz Experiment Proposal

1. Introduction

Verizon Communications Inc. (Verizon or the Company) is a holding company that, acting through its subsidiaries, is one of the world's leading providers of communications, information and entertainment products and services to consumers, businesses and governmental agencies. With a presence around the world, we offer voice, data and video services and solutions on our wireless and wireline networks that are designed to meet customers' demand for mobility, reliable network connectivity, security and control. We have two reportable segments, Wireless and Wireline. Our wireless business, operating as Verizon Wireless, provides voice and data services and equipment sales across the United States (U.S.) using one of the most extensive and reliable wireless networks.

2. Experiment Description

Verizon is working with partner companies to develop equipment that will use LTE technologies, using Citizens Band Radio Service (CBRS) spectrum, also known as Band 48, using 3GPP terminology. As part of the technology validation, Verizon plans to conduct a series of field tests with both category A and category B Citizen Band Service Devices (CBSDs) at one or more locations.

The purpose of the proposed tests is:

- 1) Evaluation of the radio propagation characteristics of 3.5 GHz for indoor and outdoor installations
- 2) Evaluation of end-to-end CBRS architecture
- 3) Evaluation of coexistence mechanisms with shared spectrum (GAA) spectrum
- 4) Evaluation of TDD-LTE using 3.5 GHz
- 5) Evaluation of inter-band carrier aggregation between 3.5 GHz and licensed bands using 3GPP Band 2 or 3GPP Band 4

Note: Verizon will limit all of the above tests to 3650-3700 MHz.

Field tests will be conducted in a production network, in a highly controlled field environment, in order to assist in the development of commercial products. The testing will benefit the public interest by enabling the pre-commercial testing of new products outside of a lab environment but in a controlled and managed manner.

In addition to the product development testing described above, Verizon and partner companies intend to conduct separate and independent lab testing in a real-world environment at a Verizon facility or at a vendor's facility using specifications developed by the WINN Forum and CBRS Alliance.

This field trial will consist of an aggregate of up to **10** small cells (category A), and up to **5** category B CBSDs, for all the trial locations. The CBSDs will use the transmission parameters and operate inside the geographic regions defined below. Some of the tests will use solely base stations and user equipment operating in CBRS spectrum only. Some equipment however, includes 3GPP LTE base stations that operate on 3GPP Band 2 or 3GPP Band 4, also known respectively as the US 1900 MHz PCS and AWS bands operated under 47 CFR Part 24 and

Part 27. Transmission on PCS or AWS spectrum will occur only with authorization from the respective spectrum licensee.

Verizon and several mobile device partner companies are planning to conduct testing with an aggregate of no more than 95 mobile devices to support the field trial testing. Typically only one mobile device partner will be participating in the tests at any given point in time, using 15-30 mobile devices. The mobile devices will operate within the RF coverage area of the small cell devices. Some of the tests with mobile stations will be using CBRS spectrum only. The majority of the tests, however, will include mobiles and base stations with LTE transmitters that operate on 3GPP Band 2, or 3GPP Band 4, in carrier aggregation mode (in both Downlink and Uplink) with Band 48.

These mobile devices will only be used by test engineers, from either Verizon or mobile device partners. They are strictly limited to field trial testing between Verizon and partner companies and will not be released to Verizon customers or consumers.

Although the initial devices are prototypes and have not completed formal equipment authorization, the equipment used in these trials will be compliant with FCC rules. As time progresses, pre-commercial devices will be introduced. Equipment from multiple equipment manufacturers will be used in the evaluation testing. Verizon has the ability to shut down all transmissions operated under the experimental license in the unlikely event any interference occurs.

3. Hours of operation and equipment shut down

The intent is to operate the evaluation devices, both small cells and mobile units, 24 hours per day, 7 days per week, during the test period. Equipment can be shut down speedily, if the need arises, by contacting one or more of the interference coordinators identified in the section "Interference Coordination"

4. Interference Coordination

Immediate requests to stop transmissions under this STA can be communicated to Jaime Lugo, Verizon Senior Manager System Performance at 561-252-8338 or by email at jaime.lugo@verizonwireless.com or Rachid Fadlallah, Verizon Principal Engineer System Performance at 954-551-5538 or by email at rachid.fadlallah@verizonwireless.com.

5. Trial Duration

Approximately one year.

6. Evaluation Equipment Transmitter Information

Small cells supporting in Band 48 will be operating in compliance with FCC Part 96 rules. Both directional and omni-directional antennas will be used with the small cell systems within the maximum EIRP and antenna gain constraints as specified in the rules.

LTE mobile devices support TDD-LTE operation with an LTE uplink in Band 48 and receive in the same band. Upon availability of mobile devices supporting inter-band carrier aggregation, CBSD devices supporting one or more of Verizon's licensed bands will be used.

- Up to **5** category B CBSDs (EIRP \leq 50 dBm/20 MHz) using Band 48
- Up to **10** category A CBSDs (EIRP \leq 33 dBm/20 MHz) using Band 48
- Multiple mobile terminals (no more than an aggregate of 95 test mobiles, from multiple mobile device partners, with only 15-30 mobile terminals radiating at a given time), each terminal operating in either standalone Band 48 only or in Carrier Aggregation (CA) mode, using licensed bands B2 or B4 or a combination of these, in CA aggregation with B48, using LTE(FDD/TDD), with a maximum transmitter power = 24 dBm

Verizon will conduct the above proposed tests at two different locations:

Boca Raton, Florida – This location will be used for indoor 3.5 GHz testing between Category A CBSDs and mobile terminals. Each Category A CBSD will utilize integrated antenna for transmission and reception.

Fort Lauderdale, Florida – This location will be used for outdoor 3.5 GHz testing between Category B CBSDs and mobile terminals. For outdoor radio installations, integrated antenna as well as directional antenna with horizontal orientation ranging from 36-degree to 360-degree in step of 36-deg (i.e. 36°, 72°, 108°, 144°, 180°, 185°, 216°, 252°, 288°, 324°, 360°) will also be evaluated for transmission and reception.