

NTIA Space Record Data Form

(Note: Apex recognizes its frequency plan’s complexity and, therefore, has summarized all inputs in its application’s [technical annex](#) (table 1 and table 2) for convenience. Apex also notes no U.S.-based earth stations will communicate with the Apex Aries 1 satellite. In other words, no space-to-Earth or Earth-to-space transmissions will occur inside the United States and Apex submits no NTIA space record data form Part B information consistent with its other application materials.)

NTIA requires the following data for space related experiments using government shared spectrum. For each transmit frequency, please provide the data for both ends of the transmit-receive link. Use Part A to describe the satellite to ground information. Part B is for all ground to space transmit links.

Part A: Space to Earth Downlink Data

| | |
|--------------------------------------|----|
| Transmit Frequency: 400.5 MHz | 2 |
| 2.64 kHz bandwidth | 2 |
| Transmit Frequency: 401.5 MHz | 10 |
| 2.64 kHz bandwidth | 10 |
| Transmit Frequency: 400.5 MHz | 18 |
| 65.28 kHz bandwidth | 18 |
| Transmit Frequency: 401.5 MHz | 26 |
| 65.28 kHz bandwidth | 26 |
| Transmit Frequency: 2287.5 MHz | 34 |
| 168.8 kHz bandwidth | 34 |
| Transmit Frequency: 2287.5 MHz | 51 |
| 1 MHz bandwidth | 51 |
| Transmit Frequency: 8212.5 MHz | 68 |
| 13.5 MHz bandwidth | 68 |
| Transmit Frequency: 8212.5 MHz | 72 |
| 100 MHz bandwidth | 72 |
| Transmit Frequency: 8212.5 MHz | 76 |
| 13.5 MHz bandwidth | 76 |
| Transmit Frequency: 8212.5 MHz | 90 |
| 100 MHz bandwidth | 90 |

| Transmit Frequency: 400.5 MHz | | |
|--------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Satellite Name: Apex Aries 1 | | |
| Data Field | Data Answer | Description/Comments |
| Transmit Power (PWR) | PWR = 1.2 W PWR01 W1.2 | TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT |
| Necessary Bandwidth | 2.64 kHz | THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL. |
| RF Emissions Data | | 2-SIDED EMISSION BANDWIDTH VALUES |
| -3 dB bandwidth | 3 kHz | |
| -20 dB bandwidth | 17.5 kHz | |
| -40 dB bandwidth | 25 kHz | |
| -60 dB bandwidth | 40 kHz | |
| Modulation Type | 2GFSK | THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK. |
| Data Rate | 1.2 kbits/sec | INFORMATION DATA RATE |
| Forward Error Correction Coding | Is FEC used? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> FEC Type: _____, FEC Rate: _____, | |
| Total Symbol Rate | 1.2 ksymbols/sec | DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR. |
| Does transmitter have a beacon mode? | Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> | BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE. |
| If transmitter has a beacon mode, can the beacon be commanded off? | Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> | |
| Transmit Antenna Polarization (XAP) | XAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Transmit Antenna Orientation (XAZ) | XAZ = EC | NB= NARROWBEAM EC = EARTH COVERAGE |
| Transmit Antenna Dimension (XAD) | ANTENNA GAIN <u>0 dBi</u> , BEAMWIDTH <u>360</u> , XAD = XAD01 00G360B | NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B |

| | | |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type of satellite (State = SPCE) (City = Geo or Nonge) | Type = NONGEOSTATIONARY | CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY |
| For Geostationary Satellites | Longitude = | IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG). |
| For Nongeostationary (Orbital Data) | INCLINATION ANGLE <u>97.4</u> , APOGEE IN KILOMETERS <u>525</u> , PERIGEE IN KILOMETERS <u>525</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>0.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB = ORB, 97.4IN00525AP00525PE001.58H01T01 | IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01 |
| For SunSynchronous Nongeostationary Orbits | Mean Local Time of Ascending Node MLTDN = 13:00 + 60 mins or 13:00-14:00 (Note: SpaceX notified use of LTDN, not LTAN.) | MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM) |
| | | |
| | | |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = South Africa | |
| City Name (RAL) | RAL = Pretoria | |
| Latitude (DDMMSS) | Lat = 255136 S | |
| Longitude (DDMMSS) | Lon = 0282700 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>16.2</u> , BEAMWIDTH <u>22</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>1339</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>6</u> , RAD = RAD01 16.2G022B000-360A01339H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>N/A</u> , ANTENNA EFFICIENCY <u>N/A</u> | |
| Number of Satellite Contacts Supported Per Day | 4 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Sweden | |
| City Name (RAL) | RAL = Boden | |
| Latitude (DDMMSS) | Lat = 654800 N | |
| Longitude (DDDMMSS) | Lon = 0214048 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ___16.2___, BEAMWIDTH ___22___, AZIMUTHAL RANGE ___360___, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ___46___, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ___6___, RAD = RAD02 16.2G022B000-360A00046H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ___N/A___, ANTENNA EFFICIENCY ___N/A___ | |
| Number of Satellite Contacts Supported Per Day | 11 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Spain | |
| City Name (RAL) | RAL = Puertollano | |
| Latitude (DDMMSS) | Lat = 384026 N | |
| Longitude (DDDMMSS) | Lon = 0040943 W | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>14.8</u> , BEAMWIDTH <u>40</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>690</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>14</u> , RAD = RAD03 14.8G040B000-360A00690H014 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>N/A</u> , ANTENNA EFFICIENCY <u>N/A</u> | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Italy | |
| City Name (RAL) | RAL = Vimercate | |
| Latitude (DDMMSS) | Lat = 453536 N | |
| Longitude (DDDMMSS) | Lon = 0092144 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN __14.8_____, BEAMWIDTH __40_____, AZIMUTHAL RANGE __000-360_____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS __177_____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS __13_____, RAD = RAD04 14.8G040B000-360A00177H013 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER __N/A_____, ANTENNA EFFICIENCY __N/A_____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Italy | |
| City Name (RAL) | RAL = Lomazzo | |
| Latitude (DDMMSS) | Lat = 454150 N | |
| Longitude (DDDMMSS) | Lon = 0090205 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN _____ 14.8 _____, BEAMWIDTH _____ 40 _____, AZIMUTHAL RANGE _____ 000-360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____ 296 _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____ 25 _____, RAD = RAD05 14.8G040B000-360A00296H025 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER _____ N/A _____, ANTENNA EFFICIENCY _____ N/A _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = United Kingdom | |
| City Name (RAL) | RAL = Unst, Shetland | |
| Latitude (DDMMSS) | Lat = 604452 N | |
| Longitude (DDDMMSS) | Lon = 0005128 W | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|--------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>14.8</u> , BEAMWIDTH <u>40</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>19</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>4</u> , RAD = RAD06 14.8G040B000-360A00019H004 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>N/A</u> , ANTENNA EFFICIENCY <u>N/A</u> | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| FCC notes: 1. Use S-Note S945. 2. REM AGN, Cubesat, (Apex Aries 1) | | |

| Transmit Frequency: 401.5 MHz | | |
|--------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Satellite Name: Apex Aries 1 | | |
| Data Field | Data Answer | Description/Comments |
| Transmit Power (PWR) | PWR = 1.2 W PWR01 W1.2 | TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT |
| Necessary Bandwidth | 2.64 kHz | THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL. |
| RF Emissions Data | | 2-SIDED EMISSION BANDWIDTH VALUES |
| -3 dB bandwidth | 3 kHz | |
| -20 dB bandwidth | 17.5 kHz | |
| -40 dB bandwidth | 25 kHz | |
| -60 dB bandwidth | 40 kHz | |
| Modulation Type | 2GFSK | THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK. |
| Data Rate | 1.2 kbits/sec | INFORMATION DATA RATE |
| Forward Error Correction Coding | Is FEC used? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> FEC Type: _____, FEC Rate: _____, | |
| Total Symbol Rate | 1.2 ksymbols/sec | DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR. |
| Does transmitter have a beacon mode? | Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> | BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE. |
| If transmitter has a beacon mode, can the beacon be commanded off? | Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> | |
| Transmit Antenna Polarization (XAP) | XAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Transmit Antenna Orientation (XAZ) | XAZ = EC | NB= NARROWBEAM EC = EARTH COVERAGE |
| Transmit Antenna Dimension (XAD) | ANTENNA GAIN <u>0 dBi</u> , BEAMWIDTH <u>360</u> , XAD = XAD01 00G360B | NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B |

| | | |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type of satellite (State = SPCE) (City = Geo or Nongeo) | Type = NONGEOSTATIONARY | CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY |
| For Geostationary Satellites | Longitude = | IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG). |
| For Nongeostationary (Orbital Data) | INCLINATION ANGLE <u>97.4</u> , APOGEE IN KILOMETERS <u>525</u> , PERIGEE IN KILOMETERS <u>525</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>0.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB = ORB, 97.4IN00525AP00525PE001.58H01T01 | IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01 |
| For SunSynchronous Nongeostationary Orbits | Mean Local Time of Ascending Node MLTDN = 13:00 + 60 mins or 13:00-14:00 (Note: SpaceX notified use of LTDN, not LTAN.) | MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM) |
| | | |
| | | |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = South Africa | |
| City Name (RAL) | RAL = Pretoria | |
| Latitude (DDMMSS) | Lat = 255136 S | |
| Longitude (DDMMSS) | Lon = 0282700 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>16.2</u> , BEAMWIDTH <u>22</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>1339</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>6</u> , RAD = RAD01 16.2G022B000-360A01339H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>N/A</u> , ANTENNA EFFICIENCY <u>N/A</u> | |
| Number of Satellite Contacts Supported Per Day | 4 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Sweden | |
| City Name (RAL) | RAL = Boden | |
| Latitude (DDMMSS) | Lat = 654800 N | |
| Longitude (DDDMMSS) | Lon = 0214048 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ___16.2___, BEAMWIDTH ___22___, AZIMUTHAL RANGE ___360___, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ___46___, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ___6___, RAD = RAD02 16.2G022B000-360A00046H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ___N/A___, ANTENNA EFFICIENCY ___N/A___ | |
| Number of Satellite Contacts Supported Per Day | 11 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Spain | |
| City Name (RAL) | RAL = Puertollano | |
| Latitude (DDMMSS) | Lat = 384026 N | |
| Longitude (DDDMMSS) | Lon = 0040943 W | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 14.8 ____ , BEAMWIDTH ____ 40 ____ , AZIMUTHAL RANGE ____ 000-360 ____ , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____ 690 ____ , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 14 ____ , RAD = RAD03 14.8G040B000-360A00690H014 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ N/A ____ , ANTENNA EFFICIENCY ____ N/A ____ , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Italy | |
| City Name (RAL) | RAL = Vimercate | |
| Latitude (DDMMSS) | Lat = 453536 N | |
| Longitude (DDDMMSS) | Lon = 0092144 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>14.8</u> , BEAMWIDTH <u>40</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>177</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>13</u> , RAD = RAD04 14.8G040B000-360A00177H013 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>N/A</u> , ANTENNA EFFICIENCY <u>N/A</u> | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Italy | |
| City Name (RAL) | RAL = Lomazzo | |
| Latitude (DDMMSS) | Lat = 454150 N | |
| Longitude (DDDMMSS) | Lon = 0090205 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 14.8 ____ , BEAMWIDTH ____ 40 ____ , AZIMUTHAL RANGE ____ 000-360 ____ , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____ 296 ____ , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 25 ____ , RAD = RAD05 14.8G040B000-360A00296H025 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ N/A ____ , ANTENNA EFFICIENCY ____ N/A ____ , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = United Kingdom | |
| City Name (RAL) | RAL = Unst, Shetland | |
| Latitude (DDMMSS) | Lat = 604452 N | |
| Longitude (DDDMMSS) | Lon = 0005128 W | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|--------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>14.8</u> , BEAMWIDTH <u>40</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>19</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>4</u> , RAD = RAD06 14.8G040B000-360A00019H004 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>N/A</u> , ANTENNA EFFICIENCY <u>N/A</u> | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| FCC notes: 1. Use S-Note S945. 2. REM AGN, Cubesat, (Apex Aries 1) | | |

| Transmit Frequency:400.5 MHz | | |
|--------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Satellite Name: Apex Aries 1 | | |
| Data Field | Data Answer | Description/Comments |
| Transmit Power (PWR) | PWR = 2 W PWR02 W2 | TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT |
| Necessary Bandwidth | 65.28 kHz | THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL. |
| RF Emissions Data | | 2-SIDED EMISSION BANDWIDTH VALUES |
| -3 dB bandwidth | 68.28 kHz | |
| -20 dB bandwidth | 82.3 kHz | |
| -40 dB bandwidth | 92 kHz | |
| -60 dB bandwidth | 105 kHz | |
| Modulation Type | 2GFSK | THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK. |
| Data Rate | 1.2 kbits/sec | INFORMATION DATA RATE |
| Forward Error Correction Coding | Is FEC used? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> FEC Type: _____, FEC Rate: _____, | |
| Total Symbol Rate | 1.2 ksymbols/sec | DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR. |
| Does transmitter have a beacon mode? | Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> | BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE. |
| If transmitter has a beacon mode, can the beacon be commanded off? | Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> | |
| Transmit Antenna Polarization (XAP) | XAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Transmit Antenna Orientation (XAZ) | XAZ = EC | NB= NARROWBEAM EC = EARTH COVERAGE |
| Transmit Antenna Dimension (XAD) | ANTENNA GAIN <u>0 dBi</u> , BEAMWIDTH <u>360</u> , XAD = XAD01 00G360B | NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B |

| | | |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type of satellite (State = SPCE) (City = Geo or Nongeo) | Type = NONGEOSTATIONARY | CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY |
| For Geostationary Satellites | Longitude = | IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG). |
| For Nongeostationary (Orbital Data) | INCLINATION ANGLE <u>97.4</u> , APOGEE IN KILOMETERS <u>525</u> , PERIGEE IN KILOMETERS <u>525</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>0.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB = ORB, 97.4IN00525AP00525PE001.58H01T01 | IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01 |
| For SunSynchronous Nongeostationary Orbits | Mean Local Time of Ascending Node MLTDN = 13:00 + 60 mins or 13:00-14:00 (Note: SpaceX notified use of LTDN, not LTAN.) | MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM) |
| | | |
| | | |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = South Africa | |
| City Name (RAL) | RAL = Pretoria | |
| Latitude (DDMMSS) | Lat = 255136 S | |
| Longitude (DDMMSS) | Lon = 0282700 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ___16.2___, BEAMWIDTH ___22___, AZIMUTHAL RANGE ___000-360___, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ___1339___, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ___6___, RAD = RAD01 16.2G022B000-360A01339H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ___N/A___, ANTENNA EFFICIENCY ___N/A___ | |
| Number of Satellite Contacts Supported Per Day | 4 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Sweden | |
| City Name (RAL) | RAL = Boden | |
| Latitude (DDMMSS) | Lat = 654800 N | |
| Longitude (DDDMMSS) | Lon = 0214048 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ___ 16.2 _____, BEAMWIDTH ___ 22 _____, AZIMUTHAL RANGE ___ 360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ___ 46 _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ___ 6 _____, RAD = RAD02 16.2G022B000-360A00046H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ___ N/A _____, ANTENNA EFFICIENCY ___ N/A _____, | |
| Number of Satellite Contacts Supported Per Day | 11 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Spain | |
| City Name (RAL) | RAL = Puertollano | |
| Latitude (DDMMSS) | Lat = 384026 N | |
| Longitude (DDDMMSS) | Lon = 0040943 W | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>14.8</u> , BEAMWIDTH <u>40</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>690</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>14</u> , RAD = RAD03 14.8G040B000-360A00690H014 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>N/A</u> , ANTENNA EFFICIENCY <u>N/A</u> | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Italy | |
| City Name (RAL) | RAL = Vimercate | |
| Latitude (DDMMSS) | Lat = 453536 N | |
| Longitude (DDDMMSS) | Lon = 0092144 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____14.8____, BEAMWIDTH ____40____, AZIMUTHAL RANGE ____000-360____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____177____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____13____, RAD = RAD04 14.8G040B001-360A00177H013 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____N/A____, ANTENNA EFFICIENCY ____N/A____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Italy | |
| City Name (RAL) | RAL = Lomazzo | |
| Latitude (DDMMSS) | Lat = 454150 N | |
| Longitude (DDDMMSS) | Lon = 0090205 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN _____ 14.8 _____, BEAMWIDTH _____ 40 _____, AZIMUTHAL RANGE _____ 000-360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____ 296 _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____ 25 _____, RAD = RAD05 14.8G040B000-360A00296H025 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER _____ N/A _____, ANTENNA EFFICIENCY _____ N/A _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = United Kingdom | |
| City Name (RAL) | RAL = Unst, Shetland | |
| Latitude (DDMMSS) | Lat = 604452 N | |
| Longitude (DDDMMSS) | Lon = 0005128 W | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|--------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>14.8</u> , BEAMWIDTH <u>40</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>19</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>4</u> , RAD = RAD06 14.8G040B000-360A00019H004 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>N/A</u> , ANTENNA EFFICIENCY <u>N/A</u> | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| FCC notes: 1. Use S-Note S945. 2. REM AGN, Cubesat, (Apex Aries 1) | | |

| | | |
|--------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Transmit Frequency: 401.5 MHz | | |
| Satellite Name: Apex Aries 1 | | |
| Data Field | Data Answer | Description/Comments |
| Transmit Power (PWR) | PWR = 2 W PWR02 W2 | TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT |
| Necessary Bandwidth | 65.28 kHz | THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL. |
| RF Emissions Data | | 2-SIDED EMISSION BANDWIDTH VALUES |
| -3 dB bandwidth | 68.28 kHz | |
| -20 dB bandwidth | 82.3 kHz | |
| -40 dB bandwidth | 92 kHz | |
| -60 dB bandwidth | 105 kHz | |
| Modulation Type | 2GFSK | THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK. |
| Data Rate | 1.2 kbits/sec | INFORMATION DATA RATE |
| Forward Error Correction Coding | Is FEC used? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> FEC Type: _____, FEC Rate: _____ | |
| Total Symbol Rate | 1.2 ksymbols/s | DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR. |
| Does transmitter have a beacon mode? | Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> | BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE. |
| If transmitter has a beacon mode, can the beacon be commanded off? | Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> | |
| Transmit Antenna Polarization (XAP) | XAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Transmit Antenna Orientation (XAZ) | XAZ = EC | NB= NARROWBEAM EC = EARTH COVERAGE |

| | | |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Transmit Antenna Dimension (XAD) | ANTENNA GAIN <u>0</u> , BEAMWIDTH <u>360</u> , XAD = XAD01 00G360B | NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B |
| Type of satellite (State = SPCE) (City = Geo or Nonge) | Type = NONGEOSTATIONARY | CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY |
| For Geostationary Satellites | Longitude = | IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG). |
| For Nongeostationary (Orbital Data) | INCLINATION ANGLE <u>97.4</u> , APOGEE IN KILOMETERS <u>525</u> , PERIGEE IN KILOMETERS <u>525</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>0.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB = ORB, 97.4IN00525AP00525PE001.58H01T01 | IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01 |
| For SunSynchronous Nongeostationary Orbits | Mean Local Time of Ascending Node MLTDN = 13:00 + 60 mins or 13:00-14:00 (Note: SpaceX notified use of LTDN, not LTAN.) | MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM) |
| | | |
| | | |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = South Africa | |
| City Name (RAL) | RAL = Pretoria | |
| Latitude (DDMMSS) | Lat = 255136 S | |
| Longitude (DDDMMSS) | Lon = 0282700 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ___16.2___, BEAMWIDTH ___22___, AZIMUTHAL RANGE ___000-360___, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ___1339___, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ___6___, RAD = RAD01 16.2G022B000-360A01339H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ___N/A___, ANTENNA EFFICIENCY ___N/A___ | |
| Number of Satellite Contacts Supported Per Day | 4 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Sweden | |
| City Name (RAL) | RAL = Boden | |
| Latitude (DDMMSS) | Lat = 654800 N | |
| Longitude (DDDMMSS) | Lon = 0214048 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>16.2</u> , BEAMWIDTH <u>22</u> , AZIMUTHAL RANGE <u>360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>46</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>6</u> , RAD = RAD02 16.2G022B000-360A00046H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>N/A</u> , ANTENNA EFFICIENCY <u>N/A</u> | |
| Number of Satellite Contacts Supported Per Day | 11 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Spain | |
| City Name (RAL) | RAL = Puertollano | |
| Latitude (DDMMSS) | Lat = 384026 N | |
| Longitude (DDDMMSS) | Lon = 0040943 W | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>14.8</u> , BEAMWIDTH <u>40</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>690</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>14</u> , RAD = RAD03 14.8G040B000-360A00690H014 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>N/A</u> , ANTENNA EFFICIENCY <u>N/A</u> | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Italy | |
| City Name (RAL) | RAL = Vimercate | |
| Latitude (DDMMSS) | Lat = 453536 N | |
| Longitude (DDDMMSS) | Lon = 0092144 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>14.8</u> , BEAMWIDTH <u>40</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>177</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>13</u> , RAD = RAD04 14.8G040B001-360A00177H013 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>N/A</u> , ANTENNA EFFICIENCY <u>N/A</u> | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Italy | |
| City Name (RAL) | RAL = Lomazzo | |
| Latitude (DDMMSS) | Lat = 454150 N | |
| Longitude (DDDMMSS) | Lon = 0090205 E | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 14.8 ____ , BEAMWIDTH ____ 40 ____ , AZIMUTHAL RANGE ____ 000-360 ____ , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____ 296 ____ , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 25 ____ , RAD = RAD05 14.8G040B000-360A00296H025 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ N/A ____ , ANTENNA EFFICIENCY ____ N/A ____ , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = United Kingdom | |
| City Name (RAL) | RAL = Unst, Shetland | |
| Latitude (DDMMSS) | Lat = 604452 N | |
| Longitude (DDDMMSS) | Lon = 0005128 W | |
| Receive Antenna Polarization (RAP) | RAP = J | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|--------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>14.8</u> , BEAMWIDTH <u>40</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>19</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>4</u> , RAD = RAD06 14.8G040B000-360A00019H004 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>N/A</u> , ANTENNA EFFICIENCY <u>N/A</u> , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| FCC notes: 1. Use S-Note S945. 2. REM AGN, Cubesat, (Apex Aries 1) | | |

| Transmit Frequency: 2287.5 MHz | | |
|--------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Satellite Name: Apex Aries 1 | | |
| Data Field | Data Answer | Description/Comments |
| Transmit Power (PWR) | PWR = 0.143 W PWR01 W0.143 | TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT |
| Necessary Bandwidth | 168.8 kHz | THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL. |
| RF Emissions Data | | 2-SIDED EMISSION BANDWIDTH VALUES |
| -3 dB bandwidth | 170 kHz | |
| -20 dB bandwidth | 200 kHz | |
| -40 dB bandwidth | 240 kHz | |
| -60 dB bandwidth | 400 kHz | |
| Modulation Type | BPSK | THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK. |
| Data Rate | 54.7 kbits/sec | INFORMATION DATA RATE |
| Forward Error Correction Coding | Is FEC used? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> FEC Type: <u>Reed-Solomon and 1/2 CC</u> , FEC Rate: <u>0.563</u> , | |
| Total Symbol Rate | 125 ksymbols/sec | DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR. |
| Does transmitter have a beacon mode? | Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> | BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE. |
| If transmitter has a beacon mode, can the beacon be commanded off? | Yes <input type="checkbox"/> No <input type="checkbox"/> | |
| Transmit Antenna Polarization (XAP) | XAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Transmit Antenna Orientation (XAZ) | XAZ = EC | NB= NARROWBEAM EC = EARTH COVERAGE |
| Transmit Antenna Dimension (XAD) | ANTENNA GAIN <u>6</u> , BEAMWIDTH <u>70</u> , XAD = XAD02 06G070B | NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B |

| | | |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type of satellite (State = SPCE) (City = Geo or Nonge) | Type = NONGEOSTATIONARY | CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY |
| For Geostationary Satellites | Longitude = | IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG). |
| For Nongeostationary (Orbital Data) | INCLINATION ANGLE <u>97.4</u> , APOGEE IN KILOMETERS <u>525</u> , PERIGEE IN KILOMETERS <u>525</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>0.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB = ORB, 97.4IN00525AP00525PE001.58H01T01 | IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01 |
| For SunSynchronous Nongeostationary Orbits | Mean Local Time of Ascending Node MLTDN = 13:00 + 60 mins or 13:00-14:00 (Note: SpaceX notified use of LTDN, not LTAN.) | MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM) |
| | | |
| | | |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = South Africa | |
| City Name (RAL) | RAL = Pretoria | |
| Latitude (DDMMSS) | Lat = 255136 S | |
| Longitude (DDMMSS) | Lon = 0282700 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>40</u> _____, BEAMWIDTH <u>0.97</u> _____, AZIMUTHAL RANGE <u>000-270</u> _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>1339</u> _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>6</u> _____, RAD = RAD07 40G.97B000-270A01339H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>6.0</u> _____, ANTENNA EFFICIENCY <u>0.5</u> _____, | |
| Number of Satellite Contacts Supported Per Day | 4 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Sweden | |
| City Name (RAL) | RAL = Boden | |
| Latitude (DDMMSS) | Lat = 654800 N | |
| Longitude (DDDMMSS) | Lon = 0214048 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>40</u> _____, BEAMWIDTH <u>0.97</u> _____, AZIMUTHAL RANGE <u>000-270</u> _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>46</u> _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>6</u> _____, RAD = RAD08 40G.97B000-270A00046H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>6.0</u> _____, ANTENNA EFFICIENCY <u>0.5</u> _____, | |
| Number of Satellite Contacts Supported Per Day | 11 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Australia | |
| City Name (RAL) | RAL = Currans Hill | |
| Latitude (DDMMSS) | Lat = 340224 S | |
| Longitude (DDDMMSS) | Lon = 1504612 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>16</u> , BEAMWIDTH <u>1.83</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>89</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>10</u> , RAD = RAD09 16G1.83B000-360A00089H010 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>5.4</u> , ANTENNA EFFICIENCY <u>0.5</u> , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Bahrain | |
| City Name (RAL) | RAL = Zallaq | |
| Latitude (DDMMSS) | Lat = 260300 | |
| Longitude (DDDMMSS) | Lon = 0503000 | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>16</u> _____, BEAMWIDTH <u>1.83</u> _____, AZIMUTHAL RANGE <u>000-360</u> _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>5</u> _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>10</u> _____, RAD = RAD10 16G1.83B000-360A00005H010 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>5.4</u> _____, ANTENNA EFFICIENCY <u>0.5</u> _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Ireland | |
| City Name (RAL) | RAL = Dublin | |
| Latitude (DDMMSS) | Lat = 532400 N | |
| Longitude (DDDMMSS) | Lon = 0061312 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u> 16 </u> , BEAMWIDTH <u> 1.83 </u> , AZIMUTHAL RANGE <u> 000-360 </u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u> 38 </u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u> 10 </u> , RAD = RAD11 16G1.83B000-360A00038H010 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u> 5.4 </u> , ANTENNA EFFICIENCY <u> 0.5 </u> , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Southern Australia | |
| City Name (RAL) | RAL = Peterborough | |
| Latitude (DDMMSS) | Lat = 325743 S | |
| Longitude (DDDMMSS) | Lon = 1385058 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 34.6 _____, BEAMWIDTH ____ 2.4 _____, AZIMUTHAL RANGE ____ 000-360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____ 540 _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 2.2 _____, RAD = RAD12 34.6G2.4B000-360A00540H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 3.7 _____, ANTENNA EFFICIENCY ____ .4965 _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Western Australia | |
| City Name (RAL) | RAL = Nangetty | |
| Latitude (DDMMSS) | Lat = 290037 S | |
| Longitude (DDDMMSS) | Lon = 1152030 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 34.6 ____ , BEAMWIDTH ____ 2.4 ____ , AZIMUTHAL RANGE ____ 000-360 ____ , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____ 270 ____ , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 2.2 ____ , RAD = RAD13 34.6G2.4B000-360A00270H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 3.7 ____ , ANTENNA EFFICIENCY ____ .4965 ____ , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Azerbaijan | |
| City Name (RAL) | RAL = Absheron | |
| Latitude (DDMMSS) | Lat = 402758 N | |
| Longitude (DDDMMSS) | Lon = 492908 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN _____ 34.6 _____, BEAMWIDTH _____ 2.4 _____, AZIMUTHAL RANGE _____ 000-360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____ 210 _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____ 2.2 _____, RAD = RAD14 34.6G2.4B000-360A00210H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER _____ 3.7 _____, ANTENNA EFFICIENCY _____ .4965 _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Bulgaria | |
| City Name (RAL) | RAL = Plana | |
| Latitude (DDMMSS) | Lat = 422858 N | |
| Longitude (DDDMMSS) | Lon = 0232643 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN _____35.8_____, BEAMWIDTH _____2.2_____, AZIMUTHAL RANGE _____000-360_____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____1106_____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____4_____, RAD = RAD15 35.8G2.2B000-360A01106H004 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER _____4.5_____, ANTENNA EFFICIENCY _____.3356_____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Iceland | |
| City Name (RAL) | RAL = Blönduós | |
| Latitude (DDMMSS) | Lat = 653850 N | |
| Longitude (DDDMMSS) | Lon = 0201445 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 34.6 _____, BEAMWIDTH ____ 2.4 _____, AZIMUTHAL RANGE ____ 000-360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____ 53 _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 2.2 _____, RAD = RAD16 34.6G2.4B000-360A00053H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 3.7 _____, ANTENNA EFFICIENCY ____ .4965 _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Italy | |
| City Name (RAL) | RAL = Vimercate | |
| Latitude (DDMMSS) | Lat = 453536 N | |
| Longitude (DDDMMSS) | Lon = 0092144 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN _____ 35 _____, BEAMWIDTH _____ 3.1 _____, AZIMUTHAL RANGE _____ 000-360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____ 177 _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____ 13 _____, RAD = RAD17 35G3.1B000-360A00177H013 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER _____ 3.7 _____, ANTENNA EFFICIENCY _____ .4965 _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Sri Lanka | |
| City Name (RAL) | RAL = Kandy | |
| Latitude (DDMMSS) | Lat = 071627 N | |
| Longitude (DDDMMSS) | Lon = 0804329 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 34.6 _____, BEAMWIDTH ____ 2.4 _____, AZIMUTHAL RANGE ____ 000-360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____ 462 _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 2.2 _____, RAD = RAD18 34.6G2.4B000-360A00462H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 3.7 _____, ANTENNA EFFICIENCY ____ .4965 _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = New Zealand | |
| City Name (RAL) | RAL = Awarua | |
| Latitude (DDMMSS) | Lat = 463141 S | |
| Longitude (DDDMMSS) | Lon = 1682245 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN__34.6_____, BEAMWIDTH__2.4_____, AZIMUTHAL RANGE__000-360_____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS __16_____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____2.2_____, RAD = RAD19 34.6G2.4B000-360A00016H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER____3.7_____, ANTENNA EFFICIENCY____.4965_____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Azores, Portugal | |
| City Name (RAL) | RAL = Santa Maria | |
| Latitude (DDMMSS) | Lat = 365951 N | |
| Longitude (DDDMMSS) | Lon = 0250814 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 34.6 _____, BEAMWIDTH ____ 2.4 _____, AZIMUTHAL RANGE ____ 000-360 ____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____ 194 _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 2.2 _____, RAD = RAD20 34.6G2.4B000-360A00194H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 3.7 _____, ANTENNA EFFICIENCY ____ .4965 _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = United Kingdom | |
| City Name (RAL) | RAL = Unst, Shetland | |
| Latitude (DDMMSS) | Lat = 604452 N | |
| Longitude (DDDMMSS) | Lon = 0005128 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|--------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>34.6</u> , BEAMWIDTH <u>2.4</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>19</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.2</u> , RAD = RAD21 34.6G2.4B000-360A00019H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>3.7</u> , ANTENNA EFFICIENCY <u>.4965</u> , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| FCC notes: 1. Use S-Note S945. 2. REM AGN, Cubesat, (Apex Aries 1) | | |

| Transmit Frequency: 2287.5 MHz | | |
|--------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Satellite Name: Apex Aries 1 | | |
| Data Field | Data Answer | Description/Comments |
| Transmit Power (PWR) | PWR = 0.85 W PWR01 W0.85 | TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT |
| Necessary Bandwidth | 1 MHz | THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL. |
| RF Emissions Data | | 2-SIDED EMISSION BANDWIDTH VALUES |
| -3 dB bandwidth | 1.02 MHz | |
| -20 dB bandwidth | 1.08 MHz | |
| -40 dB bandwidth | 1.14 MHz | |
| -60 dB bandwidth | 1.20 MHz | |
| Modulation Type | BPSK | THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK. |
| Data Rate | 54.7 kbits/sec | INFORMATION DATA RATE |
| Forward Error Correction Coding | Is FEC used? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> FEC Type: <u>Reed-Solomon and 1/2 CC</u> , FEC Rate: <u>0.563</u> , | |
| Total Symbol Rate | 125 ksymbols/sec | DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR. |
| Does transmitter have a beacon mode? | Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> | BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE. |
| If transmitter has a beacon mode, can the beacon be commanded off? | Yes <input type="checkbox"/> No <input type="checkbox"/> | |
| Transmit Antenna Polarization (XAP) | XAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Transmit Antenna Orientation (XAZ) | XAZ = EC | NB= NARROWBEAM EC = EARTH COVERAGE |
| Transmit Antenna Dimension (XAD) | ANTENNA GAIN <u>5</u> , BEAMWIDTH <u>70</u> , XAD = XAD02 05G070B | NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B |

| | | |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type of satellite (State = SPCE) (City = Geo or Nonge) | Type = NONGEOSTATIONARY | CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY |
| For Geostationary Satellites | Longitude = | IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG). |
| For Nongeostationary (Orbital Data) | INCLINATION ANGLE <u>97.4</u> , APOGEE IN KILOMETERS <u>525</u> , PERIGEE IN KILOMETERS <u>525</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>0.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB = ORB, 97.4IN00525AP00525PE001.58H01T01 | IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01 |
| For SunSynchronous Nongeostationary Orbits | Mean Local Time of Ascending Node MLTDN = 13:00 + 60 mins or 13:00-14:00 (Note: SpaceX notified use of LTDN, not LTAN.) | MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM) |
| | | |
| | | |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = South Africa | |
| City Name (RAL) | RAL = Pretoria | |
| Latitude (DDMMSS) | Lat = 255136 S | |
| Longitude (DDMMSS) | Lon = 0282700 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>40</u> _____, BEAMWIDTH <u>0.97</u> _____, AZIMUTHAL RANGE <u>000-270</u> _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>1339</u> _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>6</u> _____, RAD = RAD07 40G.97B000-270A01339H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>6.0</u> _____, ANTENNA EFFICIENCY <u>0.5</u> _____, | |
| Number of Satellite Contacts Supported Per Day | 4 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Sweden | |
| City Name (RAL) | RAL = Boden | |
| Latitude (DDMMSS) | Lat = 654800 N | |
| Longitude (DDDMMSS) | Lon = 0214048 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>40</u> , BEAMWIDTH <u>0.97</u> , AZIMUTHAL RANGE <u>000-270</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>46</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>6</u> , RAD = RAD08 40G.97B000-270A00046H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>6.0</u> , ANTENNA EFFICIENCY <u>0.5</u> , | |
| Number of Satellite Contacts Supported Per Day | 11 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Australia | |
| City Name (RAL) | RAL = Currans Hill | |
| Latitude (DDMMSS) | Lat = 340224 S | |
| Longitude (DDDMMSS) | Lon = 1504612 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>16</u> , BEAMWIDTH <u>1.83</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>89</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>10</u> , RAD = RAD09 16G1.83B000-360A00089H010 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>5.4</u> , ANTENNA EFFICIENCY <u>0.5</u> , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Bahrain | |
| City Name (RAL) | RAL = Zallaq | |
| Latitude (DDMMSS) | Lat = 260300 N | |
| Longitude (DDDMMSS) | Lon = 0503000 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>16</u> , BEAMWIDTH <u>1.83</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>5</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>10</u> , RAD = RAD10 16G1.83B000-360A00005H010 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>5.4</u> , ANTENNA EFFICIENCY <u>0.5</u> , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Ireland | |
| City Name (RAL) | RAL = Dublin | |
| Latitude (DDMMSS) | Lat = 532400 N | |
| Longitude (DDDMMSS) | Lon = 0061312 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u> 16 </u> , BEAMWIDTH <u> 1.83 </u> , AZIMUTHAL RANGE <u> 000-360 </u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u> 38 </u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u> 10 </u> , RAD = RAD11 16G1.83B000-360A00038H010 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u> 5.4 </u> , ANTENNA EFFICIENCY <u> 0.5 </u> , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Southern Australia | |
| City Name (RAL) | RAL = Peterborough | |
| Latitude (DDMMSS) | Lat = 325743 S | |
| Longitude (DDDMMSS) | Lon = 1385058 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 34.6 ____, BEAMWIDTH ____ 2.4 ____, AZIMUTHAL RANGE ____ 000-360 ____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____ 540 ____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 2.2 ____, RAD = RAD12 34.6G2.4B000-360A00540H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 3.7 ____, ANTENNA EFFICIENCY ____ .4965 ____ | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Western Australia | |
| City Name (RAL) | RAL = Nangetty | |
| Latitude (DDMMSS) | Lat = 290037 S | |
| Longitude (DDDMMSS) | Lon = 1152030 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN _____ 34.6 _____, BEAMWIDTH _____ 2.4 _____, AZIMUTHAL RANGE _____ 000-360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____ 270 _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____ 2.2 _____, RAD = RAD13 34.6G2.4B000-360A00270H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER _____ 3.7 _____, ANTENNA EFFICIENCY _____ .4965 _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Azerbaijan | |
| City Name (RAL) | RAL = Absheron | |
| Latitude (DDMMSS) | Lat = 402758 N | |
| Longitude (DDDMMSS) | Lon = 492908 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN _____ 34.6 _____, BEAMWIDTH _____ 2.4 _____, AZIMUTHAL RANGE _____ 000-360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____ 210 _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____ 2.2 _____, RAD = RAD14 34.6G2.4B000-360A00210H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER _____ 3.7 _____, ANTENNA EFFICIENCY _____ .4965 _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Bulgaria | |
| City Name (RAL) | RAL = Plana | |
| Latitude (DDMMSS) | Lat = 422858 N | |
| Longitude (DDDMMSS) | Lon = 0232643 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 35.8 _____, BEAMWIDTH ____ 2.2 _____, AZIMUTHAL RANGE ____ 000-360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____ 1106 _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 4 _____, RAD = RAD15 35.8G2.2B000-360A01106H004 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 4.5 _____, ANTENNA EFFICIENCY ____ .3356 _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Iceland | |
| City Name (RAL) | RAL = Blönduós | |
| Latitude (DDMMSS) | Lat = 653850 N | |
| Longitude (DDDMMSS) | Lon = 0201445 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 34.6 _____, BEAMWIDTH ____ 2.4 _____, AZIMUTHAL RANGE __ 000-360 __, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____ 53 _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 2.2 _____, RAD = RAD16 34.6G2.4B000-360A00053H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 3.7 _____, ANTENNA EFFICIENCY ____ .4965 _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Italy | |
| City Name (RAL) | RAL = Vimercate | |
| Latitude (DDMMSS) | Lat = 453536 N | |
| Longitude (DDDMMSS) | Lon = 0092144 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 35 ____ , BEAMWIDTH ____ 3.1 ____ , AZIMUTHAL RANGE__ 000-360____ , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____ 177 ____ , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ _13____ , RAD = RAD17 35G3.1B000-360A00177H013 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 3.0 ____ , ANTENNA EFFICIENCY ____ .4965 ____ , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Sri Lanka | |
| City Name (RAL) | RAL = Kandy | |
| Latitude (DDMMSS) | Lat = 071627 N | |
| Longitude (DDDMMSS) | Lon = 0804329 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 34.6 ____, BEAMWIDTH ____ 2.4 ____, AZIMUTHAL RANGE ____ 000-360 ____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _462 ____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 2.2 ____, RAD = RAD18 34.6G2.4B000-360A00462H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 3.7 ____, ANTENNA EFFICIENCY ____ .4965 ____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = New Zealand | |
| City Name (RAL) | RAL = Awarua | |
| Latitude (DDMMSS) | Lat = 463141 S | |
| Longitude (DDDMMSS) | Lon = 1682245 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 34.6 ____ , BEAMWIDTH ____ 2.4 ____ , AZIMUTHAL RANGE ____ 000-360 ____ , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____ 16 ____ , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 2.2 ____ , RAD = RAD19 34.6G2.4B000-360A00016H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 3.7 ____ , ANTENNA EFFICIENCY ____ .4965 ____ , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Azores, Portugal | |
| City Name (RAL) | RAL = Santa Maria | |
| Latitude (DDMMSS) | Lat = 365951 N | |
| Longitude (DDDMMSS) | Lon = 0250814 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ___ 34.6 ____, BEAMWIDTH ___ 2.4 ____, AZIMUTHAL RANGE ___ 000-360 ____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ___ 194 ____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ___ 2.2 ____, RAD = RAD20 34.6G2.4B000-360A00194H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ___ 3.7 ____, ANTENNA EFFICIENCY ___ .4965 ____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = United Kingdom | |
| City Name (RAL) | RAL = Unst, Shetland | |
| Latitude (DDMMSS) | Lat = 604452 N | |
| Longitude (DDDMMSS) | Lon = 0005128 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|--------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 34.6 ____ , BEAMWIDTH ____ 2.4 ____ , AZIMUTHAL RANGE ____ 000-360 ____ , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____ 19 ____ , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 2.2 ____ , RAD = RAD21 34.6G2.4B000-360A00019H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 3.7 ____ , ANTENNA EFFICIENCY ____ .4965 ____ , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input checked="" type="checkbox"/> Mission Payload Data <input type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| FCC notes: 1. Use S-Note S945. 2. REM AGN, Cubesat, (Apex Aries 1) | | |

| Transmit Frequency: 8212.5 MHz | | |
|--------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Satellite Name: Apex Aries 1 | | |
| Data Field | Data Answer | Description/Comments |
| Transmit Power (PWR) | PWR = 1 W PWR01 W1 | TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT |
| Necessary Bandwidth | 13.5 MHz | THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL. |
| RF Emissions Data | | 2-SIDED EMISSION BANDWIDTH VALUES |
| -3 dB bandwidth | 65 MHz | |
| -20 dB bandwidth | 75 MHz | |
| -40 dB bandwidth | 85 MHz | |
| -60 dB bandwidth | 100 MHz | |
| Modulation Type | 16APSK | THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK. |
| Data Rate | 103 mbits/sec | INFORMATION DATA RATE |
| Forward Error Correction Coding | Is FEC used? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> FEC Type: <u>LDPC 2/3</u> , FEC Rate: <u>0.67</u> , | |
| Total Symbol Rate | 69.01 msymbol/s | DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR. |
| Does transmitter have a beacon mode? | Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> | BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE. |
| If transmitter has a beacon mode, can the beacon be commanded off? | Yes <input type="checkbox"/> No <input type="checkbox"/> | |
| Transmit Antenna Polarization (XAP) | XAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Transmit Antenna Orientation (XAZ) | XAZ = EC | NB= NARROWBEAM EC = EARTH COVERAGE |
| Transmit Antenna Dimension (XAD) | ANTENNA GAIN <u>17 dBi</u> , BEAMWIDTH <u>18</u> , XAD = XAD03 17G018B | NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type of satellite (State = SPCE) (City = Geo or Nonge) | Type = NONGEOSTATIONARY | CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY |
| For Geostationary Satellites | Longitude = | IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG). |
| For Nongeostationary (Orbital Data) | INCLINATION ANGLE <u>97.4deg</u> , APOGEE IN KILOMETERS <u>525 km</u> , PERIGEE IN KILOMETERS <u>525 km</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>0.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB = ORB, 97.4IN00525AP00525PE001.58H01T01 | IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01 |
| For SunSynchronous Nongeostationary Orbits | Mean Local Time of Ascending Node MLTDN = 13:00 + 60 mins or 13:00-14:00 (Note: SpaceX notified use of LTDN, not LTAN.) | MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM) |
| | | |
| | | |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = South Africa | |
| City Name (RAL) | RAL = Pretoria | |
| Latitude (DDMMSS) | Lat = 255136 S | |
| Longitude (DDMMSS) | Lon = 0282700 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 52 ____ , BEAMWIDTH ____ 0.2 ____ , AZIMUTHAL RANGE _000-270____ , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _1339____ , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 6 ____ , RAD = RAD22 52G0.2B000-270A01339H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 6.0 ____ , ANTENNA EFFICIENCY ____ 0.5 ____ , | |
| Number of Satellite Contacts Supported Per Day | 4 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Sweden | |
| City Name (RAL) | RAL = Boden | |
| Latitude (DDMMSS) | Lat = 654800 N | |
| Longitude (DDDMMSS) | Lon = 0214048 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|--------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>52</u> , BEAMWIDTH <u>0.2</u> , AZIMUTHAL RANGE <u>000-270</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>46</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>6</u> , RAD = RAD23 52G0.2B000-270A00046H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>6.0</u> , ANTENNA EFFICIENCY <u>0.5</u> , | |
| Number of Satellite Contacts Supported Per Day | 11 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| FCC notes: 1. Use S-Note S945. 2. REM AGN, Cubesat, (Apex Aries 1) | | |

| Transmit Frequency: 8212.5 MHz | | |
|--------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Satellite Name: Apex Aries 1 | | |
| Data Field | Data Answer | Description/Comments |
| Transmit Power (PWR) | PWR = 2 W PWR01 W2 | TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT |
| Necessary Bandwidth | 100 MHz | THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL. |
| RF Emissions Data | | 2-SIDED EMISSION BANDWIDTH VALUES |
| -3 dB bandwidth | 65 MHz | |
| -20 dB bandwidth | 75 MHz | |
| -40 dB bandwidth | 85 MHz | |
| -60 dB bandwidth | 100 MHz | |
| Modulation Type | 16APSK | THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK. |
| Data Rate | 103 mbits/sec | INFORMATION DATA RATE |
| Forward Error Correction Coding | Is FEC used? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> FEC Type: <u>LDPC 2/3</u> , FEC Rate: <u>0.67</u> , | |
| Total Symbol Rate | 69.01 msymbols/sec | DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR. |
| Does transmitter have a beacon mode? | Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> | BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE. |
| If transmitter has a beacon mode, can the beacon be commanded off? | Yes <input type="checkbox"/> No <input type="checkbox"/> | |
| Transmit Antenna Polarization (XAP) | XAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Transmit Antenna Orientation (XAZ) | XAZ = EC | NB= NARROWBEAM EC = EARTH COVERAGE |
| Transmit Antenna Dimension (XAD) | ANTENNA GAIN <u>17 dBi</u> , BEAMWIDTH <u>18</u> , XAD = XAD03 17G018B | NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B |

| | | |
|--------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type of satellite (State = SPCE) (City = Geo or Nonge) | Type = NONGEOSTATIONARY | CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY |
| For Geostationary Satellites | Longitude = | IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG). |
| For Nongeostationary (Orbital Data) | INCLINATION ANGLE <u>97.4deg</u> , APOGEE IN KILOMETERS <u>525 km</u> , PERIGEE IN KILOMETERS <u>525 km</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>0.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB = ORB, 97.4IN00525AP00525PE001.58H01T01 | IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01 |
| For SunSynchronous Nongeostationary Orbits | Mean Local Time of Ascending Node MLTDN = 13:00 + 60 mins or 13:00-14:00 (Note: SpaceX notified use of LTDN, not LTAN.) | MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM) |

Earth Station Data (Receiver) at Each Earth Station Location

| | | |
|------------------------------------|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| State (RSC) | RSC = South Africa | |
| City Name (RAL) | RAL = Pretoria | |
| Latitude (DDMMSS) | Lat = 255136 S | |
| Longitude (DDDMMSS) | Lon = 0282700 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 52 ____ , BEAMWIDTH ____ 0.2 ____ , AZIMUTHAL RANGE _000-270____ , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _1339____ , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 6 ____ , RAD = RAD22 52G0.2B000-270A01339H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 6.0 ____ , ANTENNA EFFICIENCY ____ 0.5 ____ , | |
| Number of Satellite Contacts Supported Per Day | 4 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Sweden | |
| City Name (RAL) | RAL = Boden | |
| Latitude (DDMMSS) | Lat = 654800 N | |
| Longitude (DDDMMSS) | Lon = 0214048 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|--------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>52</u> , BEAMWIDTH <u>0.2</u> , AZIMUTHAL RANGE <u>000-270</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>46</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>6</u> , RAD = RAD23 52G0.2B000-270A00046H006 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>6.0</u> , ANTENNA EFFICIENCY <u>0.5</u> , | |
| Number of Satellite Contacts Supported Per Day | 11 contacts per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| FCC notes: 1. Use S-Note S945. 2. REM AGN, Cubesat, (Apex Aries 1) | | |

| Transmit Frequency: 8212.5 MHz | | |
|--------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Satellite Name: Apex Aries 1 | | |
| Data Field | Data Answer | Description/Comments |
| Transmit Power (PWR) | PWR = 1 W PWR02 W1 | TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT |
| Necessary Bandwidth | 13.5 MHz | THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL. |
| RF Emissions Data | | 2-SIDED EMISSION BANDWIDTH VALUES |
| -3 dB bandwidth | 65 MHz | |
| -20 dB bandwidth | 75 MHz | |
| -40 dB bandwidth | 85 MHz | |
| -60 dB bandwidth | 100 MHz | |
| Modulation Type | 16APSK | THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK. |
| Data Rate | 103 mbits/sec | INFORMATION DATA RATE |
| Forward Error Correction Coding | Is FEC used? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> FEC Type: <u>LDPC 2/3</u> , FEC Rate: <u>0.67</u> , | |
| Total Symbol Rate | 69.01 msymbols/s | DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR. |
| Does transmitter have a beacon mode? | Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> | BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE. |
| If transmitter has a beacon mode, can the beacon be commanded off? | Yes <input type="checkbox"/> No <input type="checkbox"/> | |
| Transmit Antenna Polarization (XAP) | XAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Transmit Antenna Orientation (XAZ) | XAZ = EC | NB= NARROWBEAM EC = EARTH COVERAGE |
| Transmit Antenna Dimension (XAD) | ANTENNA GAIN <u>17 dBi</u> , BEAMWIDTH <u>18</u> , XAD = XAD03 17G018B | NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type of satellite (State = SPCE) (City = Geo or Nongeo) | Type = NONGEOSTATIONARY | CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY |
| For Geostationary Satellites | Longitude = | IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG). |
| For Nongeostationary (Orbital Data) | INCLINATION ANGLE <u>97.4deg</u> , APOGEE IN KILOMETERS <u>525 km</u> , PERIGEE IN KILOMETERS <u>525 km</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>0.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB = ORB, 97.4IN00525AP00525PE001.58H01T01 | IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01 |
| For SunSynchronous Nongeostationary Orbits | Mean Local Time of Ascending Node MLTDN = 13:00 + 60 mins or 13:00-14:00 (Note: SpaceX notified use of LTDN, not LTAN.) | MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM) |
| | | |
| | | |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Australia | |
| City Name (RAL) | RAL = Currans Hill | |
| Latitude (DDMMSS) | Lat = 340224 S | |
| Longitude (DDMMSS) | Lon = 1504612 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 30.5 ____ , BEAMWIDTH ____ 0.46 ____ , AZIMUTHAL RANGE _000-360____ , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _89____ , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 10 ____ , RAD = RAD24 30G.46B000-360A00089H010 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 5.4 ____ , ANTENNA EFFICIENCY ____ 0.5 ____ , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Bahrain | |
| City Name (RAL) | RAL = Zallaq | |
| Latitude (DDMMSS) | Lat = 260300 N | |
| Longitude (DDDMMSS) | Lon = 0503000 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____30.5____, BEAMWIDTH ____0.46____, AZIMUTHAL RANGE_000-360____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS __5____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____10____, RAD = RAD25 30G.46B000-360A00005H010 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER____5.4____, ANTENNA EFFICIENCY____0.5____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Ireland | |
| City Name (RAL) | RAL = Dublin | |
| Latitude (DDMMSS) | Lat = 532400 N | |
| Longitude (DDDMMSS) | Lon = 0061312 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 30.5 ____ , BEAMWIDTH ____ 0.46 ____ , AZIMUTHAL RANGE _000-360____ , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _38____ , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 10 ____ , RAD = RAD26 30G.46B000-360A00038H010 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 5.4 ____ , ANTENNA EFFICIENCY ____ 0.5 ____ , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Southern Australia | |
| City Name (RAL) | RAL = Peterborough | |
| Latitude (DDMMSS) | Lat = 325743 S | |
| Longitude (DDDMMSS) | Lon = 1385058 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN __47_____, BEAMWIDTH __0.6_____, AZIMUTHAL RANGE __000-360____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS __540_____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS __2.2_____, RAD = RAD27 47G.60B000-360A00540H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER __3.7_____, ANTENNA EFFICIENCY __0.4965_____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Western Australia | |
| City Name (RAL) | RAL = Nangetty | |
| Latitude (DDMMSS) | Lat = 290037 S | |
| Longitude (DDDMMSS) | Lon = 1152030 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u> 47 </u> , BEAMWIDTH <u> 0.60 </u> , AZIMUTHAL RANGE <u> 000-360 </u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u> 270 </u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u> 4.0 </u> , RAD = RAD28 47G.60B000-360A00270H004 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u> 3.7 </u> , ANTENNA EFFICIENCY <u> 0.4965 </u> , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Azerbaijan | |
| City Name (RAL) | RAL = Absheron | |
| Latitude (DDMMSS) | Lat = 402758 N | |
| Longitude (DDDMMSS) | Lon = 492908 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN __ 47 ____, BEAMWIDTH __ 0.6 ____, AZIMUTHAL RANGE __ 000-360 ____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS __ 210 ____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS __ 4.0 ____, RAD = RAD29 47G.60B000-360A00210H004 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER __ 3.7 ____, ANTENNA EFFICIENCY __ 0.4965 ____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Bulgaria | |
| City Name (RAL) | RAL = Plana | |
| Latitude (DDMMSS) | Lat = 422858 N | |
| Longitude (DDDMMSS) | Lon = 0232643 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____47____, BEAMWIDTH ____0.63____, AZIMUTHAL RANGE __000-360____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____1106____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____4____, RAD = RAD30 47G.63B000-360A01106H004 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____4.5____, ANTENNA EFFICIENCY ____0.3356____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Iceland | |
| City Name (RAL) | RAL = Blönduós | |
| Latitude (DDMMSS) | Lat = 653850 N | |
| Longitude (DDDMMSS) | Lon = 0201445 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>47</u> _____, BEAMWIDTH <u>0.60</u> _____, AZIMUTHAL RANGE <u>000-360</u> _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>53</u> _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.2</u> _____, RAD = RAD31 47G.60B000-360A00053H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>3.7</u> _____, ANTENNA EFFICIENCY <u>0.4965</u> _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Sri Lanka | |
| City Name (RAL) | RAL = Kandy | |
| Latitude (DDMMSS) | Lat = 071627 N | |
| Longitude (DDDMMSS) | Lon = 0804329 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>47</u> _____, BEAMWIDTH <u>0.60</u> _____, AZIMUTHAL RANGE <u>000-360</u> _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>462</u> _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.2</u> _____, RAD = RAD32 47G.60B000-360A00462H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>3.7</u> _____, ANTENNA EFFICIENCY <u>0.4965</u> _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = New Zealand | |
| City Name (RAL) | RAL = Awarua | |
| Latitude (DDMMSS) | Lat = 463141 S | |
| Longitude (DDDMMSS) | Lon = 1682245 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>47</u> _____, BEAMWIDTH <u>0.60</u> _____, AZIMUTHAL RANGE <u>000-360</u> _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>16</u> _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.2</u> _____, RAD = RAD33 47G.60B000-360A00016H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>3.7</u> _____, ANTENNA EFFICIENCY <u>0.4965</u> _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Azores, Portugal | |
| City Name (RAL) | RAL = Santa Maria | |
| Latitude (DDMMSS) | Lat = 365951 N | |
| Longitude (DDDMMSS) | Lon = 0250814 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>47</u> _____, BEAMWIDTH <u>0.60</u> _____, AZIMUTHAL RANGE <u>000-360</u> _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>194</u> _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.2</u> _____, RAD = RAD34 47G.60B000-360A00194H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>3.7</u> _____, ANTENNA EFFICIENCY <u>0.4965</u> _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = United Kingdom | |
| City Name (RAL) | RAL = Unst, Shetland | |
| Latitude (DDMMSS) | Lat = 604452 N | |
| Longitude (DDDMMSS) | Lon = 0005128 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|--------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN _____ 47 _____, BEAMWIDTH _____ 0.6 _____, AZIMUTHAL RANGE _____ 000-360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____ 19 _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____ 2.2 _____, RAD = RAD35 47G.60B000-360A00019H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER _____ 3.7 _____, ANTENNA EFFICIENCY _____ 0.4965 _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| FCC notes: 1. Use S-Note S945. 2. REM AGN, Cubesat, (Apex Aries 1) | | |

| Transmit Frequency: 8212.5 MHz | | |
|--------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Satellite Name: Apex Aries 1 | | |
| Data Field | Data Answer | Description/Comments |
| Transmit Power (PWR) | PWR = 2 W PWR02 W2 | TRANSMIT POWER SUPPLIED TO THE ANTENNA INPUT TERMINAL, EXAMPLE, PWR01 W2 TRANSMIT POWER UNITS INCLUDE: W = WATT, K = KILOWATT, M = MEGAWATT |
| Necessary Bandwidth | 100 MHz | THE WIDTH OF FREQUENCY BAND WHICH IS JUST SUFFICIENT TO SUCCESSFULLY TRANSFER DATA. FORMULAS CAN BE FOUND IN ANNEX J OF THE NTIA MANUAL. |
| RF Emissions Data | | 2-SIDED EMISSION BANDWIDTH VALUES |
| -3 dB bandwidth | 65 MHz | |
| -20 dB bandwidth | 75 MHz | |
| -40 dB bandwidth | 85 MHz | |
| -60 dB bandwidth | 100 MHz | |
| Modulation Type | 16APSK | THE METHOD USED TO SUPERIMPOSE DATA ON THE CARRIER, EXAMPLE, BPSK, QPSK, GMSK. |
| Data Rate | 103 mbits/sec | INFORMATION DATA RATE |
| Forward Error Correction Coding | Is FEC used? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> FEC Type: <u>LDPC 2/3</u> , FEC Rate: <u>0.67</u> , | |
| Total Symbol Rate | 69.01 Msymbols/sec | DATA RATE COMBINED WITH FEC AND FRAME OVERHEAD RESULTING IN THE TOTAL SYMBOL RATE AT THE INPUT TO THE SYMBOL MAPPER/MODULATOR. |
| Does transmitter have a beacon mode? | Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> | BEACON MODE IS NORMALLY CONSIDERED A REGULAR AND PERIODIC SHORT DURATION TRANSMISSION THAT IS OFTEN USED TO ASSIST WITH TRACKING, DOPPLER COMPENSATION, OR SMALL SATELLITE IDENTIFICATION WHOSE TRANSMISSIONS ARE NOT LIMITED TO DURATIONS WHEN SUPPORTING GROUND STATIONS ARE VISIBLE. |
| If transmitter has a beacon mode, can the beacon be commanded off? | Yes <input type="checkbox"/> No <input type="checkbox"/> | |
| Transmit Antenna Polarization (XAP) | XAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Transmit Antenna Orientation (XAZ) | XAZ = EC | NB= NARROWBEAM EC = EARTH COVERAGE |
| Transmit Antenna Dimension (XAD) | ANTENNA GAIN <u>17 dBi</u> , BEAMWIDTH <u>18</u> , XAD = XAD03 17G018B | NTIA FORMAT (XAD), EXAMPLE, FOR 16 DBI ANTENNA GAIN AND 30 DEGREE BEAMWIDTH XAD01 16G030B |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type of satellite (State = SPCE) (City = Geo or Nongeo) | Type = NONGEOSTATIONARY | CHOOSE EITHER: GEOSTATIONARY OR NONGEOSTATIONARY |
| For Geostationary Satellites | Longitude = | IF ANY SATELLITES ARE GEOSTATIONARY, REPORT ITS LATITUDE AS 000000N (XLA AND/OR RLA) AND REPORT ITS LONGITUDE IN DDDMMSS FORMAT (XLG AND/OR RLG). |
| For Nongeostationary (Orbital Data) | INCLINATION ANGLE <u>97.4deg</u> , APOGEE IN KILOMETERS <u>525 km</u> , PERIGEE IN KILOMETERS <u>525 km</u> , ORBITAL PERIOD IN HOURS <u>1</u> AND FRACTIONS OF HOURS IN DECIMAL <u>0.58</u> , THE NUMBER OF SATELLITES IN THE SYSTEM <u>1</u> , ORB = ORB, 97.4IN00525AP00525PE001.58H01T01 | IF ANY SATELLITES ARE NONGEOSTATIONARY, REPORT ITS INCLINATION ANGLE, APOGEE IN KILOMETERS, PERIGEE IN KILOMETERS, ORBITAL PERIOD IN HOURS AND FRACTIONS OF HOURS IN DECIMAL, THE NUMBER OF SATELLITES IN THE SYSTEM, THEN T01, EXAMPLE, REM04 *ORB,98.0IN00510AP00510PE001.58H01NRT01, AND FOR SPACE-TO-SPACE COMMUNICATIONS WITH ANOTHER NONGEOSTATIONARY SATELLITE ADD AN ADDITIONAL *ORB FOR IT ENDING IN R01, EXAMPLE, REM05 *ORB,72.9IN03209AP00655PE013.46H01NRR01 |
| For SunSynchronous Nongeostationary Orbits | Mean Local Time of Ascending Node MLTDN = 13:00 + 60 mins or 13:00-14:00 (Note: SpaceX notified use of LTDN, not LTAN.) | MLTAN IS THE ANGLE BETWEEN AN ORBIT'S ASCENDING NODE AND THE MEAN SUN, OFTEN EXPRESSED AS UNIT OF TIME (HH:MM) |
| | | |
| | | |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Australia | |
| City Name (RAL) | RAL = Currans Hill | |
| Latitude (DDMMSS) | Lat = 340224 S | |
| Longitude (DDMMSS) | Lon = 1504612 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____ 30.5 ____ , BEAMWIDTH ____ 0.46 ____ , AZIMUTHAL RANGE_ 000-360 ____ , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS ____ 89 ____ , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____ 10 ____ , RAD = RAD24 30.5G.46B000-360A00089H010 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER ____ 5.4 ____ , ANTENNA EFFICIENCY ____ 0.5 ____ , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Bahrain | |
| City Name (RAL) | RAL = Zallaq | |
| Latitude (DDMMSS) | Lat = 260300 N | |
| Longitude (DDDMMSS) | Lon = 0503000 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____30.5____, BEAMWIDTH ____0.46____, AZIMUTHAL RANGE_000-360____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS __5____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____10____, RAD = RAD25 30.5G.46B000-360A00005H010 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER____5.4____, ANTENNA EFFICIENCY____0.5____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Ireland | |
| City Name (RAL) | RAL = Dublin | |
| Latitude (DDMMSS) | Lat = 532400 N | |
| Longitude (DDDMMSS) | Lon = 0061312 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN ____30.5____, BEAMWIDTH ____0.46____, AZIMUTHAL RANGE_000-360____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _38____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS ____10____, RAD = RAD26 30.5G.46B000-360A00038H010 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER____5.4____, ANTENNA EFFICIENCY____0.5____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Southern Australia | |
| City Name (RAL) | RAL = Peterborough | |
| Latitude (DDMMSS) | Lat = 325743 S | |
| Longitude (DDDMMSS) | Lon = 1385058 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN __ 47 ____, BEAMWIDTH __ 0.6 ____, AZIMUTHAL RANGE __ 000-360 ____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS __ 540 ____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS __ 2.2 ____, RAD = RAD27 47G.60B000-360A00540H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER __ 3.7 ____, ANTENNA EFFICIENCY __ 0.4965 ____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Western Australia | |
| City Name (RAL) | RAL = Nangetty | |
| Latitude (DDMMSS) | Lat = 290037 S | |
| Longitude (DDDMMSS) | Lon = 1152030 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>47</u> _____, BEAMWIDTH <u>0.60</u> _____, AZIMUTHAL RANGE <u>000-360</u> _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>270</u> _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.2</u> _____, RAD = RAD28 47G.60B000-360A00270H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>3.7</u> _____, ANTENNA EFFICIENCY <u>0.4965</u> _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Azerbaijan | |
| City Name (RAL) | RAL = Absheron | |
| Latitude (DDMMSS) | Lat = 402758 N | |
| Longitude (DDDMMSS) | Lon = 492908 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>47</u> _____, BEAMWIDTH <u>0.60</u> _____, AZIMUTHAL RANGE <u>000-360</u> _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>210</u> _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.2</u> _____, RAD = RAD29 47G.60B000-360A00210H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>3.7</u> _____, ANTENNA EFFICIENCY <u>0.4965</u> _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Bulgaria | |
| City Name (RAL) | RAL = Plana | |
| Latitude (DDMMSS) | Lat = 422858 N | |
| Longitude (DDDMMSS) | Lon = 0232643 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN _____ 47 _____, BEAMWIDTH _____ 0.63 _____, AZIMUTHAL RANGE _____ 000-360 _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS _____ 1106 _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS _____ 4 _____, RAD = RAD30 47G.63B000-360A01106H004 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER _____ 4.5 _____, ANTENNA EFFICIENCY _____ 0.3356 _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Iceland | |
| City Name (RAL) | RAL = Blönduós | |
| Latitude (DDMMSS) | Lat = 653850 N | |
| Longitude (DDDMMSS) | Lon = 0201445 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>47</u> _____, BEAMWIDTH <u>0.60</u> _____, AZIMUTHAL RANGE <u>000-360</u> _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>53</u> _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.2</u> _____, RAD = RAD31 47G.60B000-360A00053H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>3.7</u> _____, ANTENNA EFFICIENCY <u>0.4965</u> _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Sri Lanka | |
| City Name (RAL) | RAL = Kandy | |
| Latitude (DDMMSS) | Lat = 071627 N | |
| Longitude (DDDMMSS) | Lon = 0804329 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>47</u> _____, BEAMWIDTH <u>0.60</u> _____, AZIMUTHAL RANGE <u>000-360</u> _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>462</u> _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.2</u> _____, RAD = RAD32 47G.60B000-360A00462H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>3.7</u> _____, ANTENNA EFFICIENCY <u>0.4965</u> _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = New Zealand | |
| City Name (RAL) | RAL = Awarua | |
| Latitude (DDMMSS) | Lat = 463141 S | |
| Longitude (DDDMMSS) | Lon = 1682245 E | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>47</u> _____, BEAMWIDTH <u>0.60</u> _____, AZIMUTHAL RANGE <u>000-360</u> _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>16</u> _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.2</u> _____, RAD = RAD33 47G.60B000-360A00016H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>3.7</u> _____, ANTENNA EFFICIENCY <u>0.4965</u> _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = Azores, Portugal | |
| City Name (RAL) | RAL = Santa Maria | |
| Latitude (DDMMSS) | Lat = 365951 N | |
| Longitude (DDDMMSS) | Lon = 0250814 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|---------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>47</u> _____, BEAMWIDTH <u>0.60</u> _____, AZIMUTHAL RANGE <u>000-360</u> _____, THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>194</u> _____, THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.2</u> _____, RAD = RAD34 47G.60B000-360A00194H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>3.7</u> _____, ANTENNA EFFICIENCY <u>0.4965</u> _____, | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| Earth Station Data (Receiver) at Each Earth Station Location | | |
| State (RSC) | RSC = United Kingdom | |
| City Name (RAL) | RAL = Unst, Shetland | |
| Latitude (DDMMSS) | Lat = 604452 N | |
| Longitude (DDDMMSS) | Lon = 0005128 W | |
| Receive Antenna Polarization (RAP) | RAP = R | POLARIZATIONS INCLUDE: H = HORIZONTAL, V = VERTICAL, S = HORIZONTAL AND VERTICAL, L = LEFT HAND CIRCULAR, R = RIGHT HAND CIRCULAR, T = RIGHT AND LEFT HAND CIRCULAR, J = LINEAR POLARIZATION |
| Receive Antenna Orientation (RAZ) | RAZ = RAZ01 V00 | THE EARTH STATION RECEIVER ANTENNA MINIMUM OPERATING ANGLE OF ELEVATION (RAZ), V00 TO V90, EXAMPLE, RAZ01 V00 |

| | | |
|--------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Receive Antenna Dimensions (RAD) | ANTENNA GAIN <u>47</u> , BEAMWIDTH <u>0.6</u> , AZIMUTHAL RANGE <u>000-360</u> , THE SITE ELEVATION ABOVE MEAN SEA LEVEL IN METERS <u>19</u> , THE ANTENNA HEIGHT ABOVE TERRAIN IN METERS <u>2.2</u> , RAD = RAD35 47G.60B000-360A00019H2.2 | EXAMPLE ASSUMING NONGEOSTATIONARY, 16 DBI GAIN, 30 DEGREE BEAMWIDTH, AZIMUTHAL RANGE FROM 001-360, SITE ELEVATION OF 357 METERS, AND ANTENNA HEIGHT ABOVE TERRAIN OF 6 METERS: RAD01 16G030B001-360A00357H006 |
| Receive Antenna Additional Information (For Parabolic Antennas) | ANTENNA DIAMETER <u>3.7</u> , ANTENNA EFFICIENCY <u>0.4965</u> , | |
| Number of Satellite Contacts Supported Per Day | <1 contact per day | NUMBER OF TIMES THE SATELLITE WILL COMMUNICATE WITH THE EARTH STATION IN THE SPACE TO EARTH DIRECTION (DOWNLINKS) EACH DAY |
| Expected Duration of Each Contact | 8 minutes | AVERAGE DURATION OF EACH CONTACT |
| Supported Operations | Satellite Health and Status Data <input type="checkbox"/> Mission Payload Data <input checked="" type="checkbox"/> | SATELLITE HEALTH AND STATUS TELEMETRY AND/OR MISSION PAYLOAD DATA |
| FCC notes: 1. Use S-Note S945. 2. REM AGN, Cubesat, (Apex Aries 1) | | |