

\$\$ADD NG T221254  
TYP01 N  
DAT01 230331  
CLA01 U  
FRQ01 M1090.0000  
EXD01 240422  
STC01 XD  
EMS01 22M00M1D  
PWR01 W.00300  
STC02 XD  
EMS02 8M00M1D  
PWR02 W.00300  
XSC01 FL  
XAL01 EQGLIN AFB  
XLA01 302335N  
XLG01 0864525W  
XAD01 13.8GCOLLNRARRY00001H0001T  
XAP01 H  
XAZ01 ND  
RSC01 FL  
RAL01 EQGLIN AFB  
RLA01 302335N  
RLG01 0864525W  
RAD01 13.8GCOLLNRARRY 0001T  
RAP01 H  
RAZ01 ND  
BUR01 FCC  
BIN01  
REM01 \*PRR,0-425  
REM02 \*RAD,0030,0016NM,B  
REM03 \*EQT,C,RAY AEROFLEX APM-424(V)5 ,PD30  
REM04 \*EQR,C,RAY AEROFLEX APM-424(V)5  
REM05 \*NTS,M018,FAA ,230331,AJIMENE,NG T221254  
SUP01 THIS (AEROFLEX) APM-424 (V5) TEST SET WILL FUNCTION AS A PARROT FOR THE  
  
SUP02 RAYTHEON MODEL 5800 INTERROGATOR THAT IS STILL UNDER DEVELOPMENT.  
THE AP  
SUP03 M-424 OPERATE USING MODES 1,2,3/A,C, AND 5. MODE C ALTITUDE SETTING WILL  
SUP04 BE SET TO AT LEAST 1000 FT BELOW GROUND LEVEL OR AT LEAST 90,000 FT AB  
SUP05 OVE GROUND LEVEL (-1000 OR 90,000 FT). COORDINATE WITH LOCAL ATC FOR A  
M

SUP06 ODE A3 BEACON CODE. STOP BUZZER POC JOHN ADAMS 8033180021 OR  
7142625019.