

\$\$ADD NG T221232
TYP01 N
DAT01 230330
CLA01 U
FRQ01 M1090.0000
EXD01 240422
STC01 XD
EMS01 22M00M1D
PWR01 W.00300
STC02 XD
EMS02 8M00M1D
PWR02 W.00300
XSC01 MS
XAL01 FOREST
XLA01 322122N
XLG01 0892414W
XAD01 13.8GCOLLRARRY00136H0001T
XAZ01 ND
RSC01 MS
RAL01 FOREST
RLA01 322122N
RLG01 0892414W
RAD01 13.8GCOLLRARRY 0001T
RAZ01 ND
BUR01 FCC
BIN01
REM01 *PRR,0-425
REM02 *RAD,0009,0005NM,B
REM03 *EQT,C,RAY AEROFLEX APM-424(V)5 ,PD30
REM04 *EQR,C,RAY AEROFLEX APM-424(V)5
REM05 *NTS,M018,FAA ,230330,AJIMENE,NG T221232
SUP01 THIS (AEROFLEX) APM-424 (V5) TEST SET WILL FUNCTION AS A PARROT FOR THE

SUP02 RAYTHEON MODEL 5800 INTERROGATOR THAT IS STILL UNDER DEVELOPMENT.
THE AP
SUP03 M-424 OPERATE USING MODES 1,2,3/A,C, AND 5. MODE C ALTITUDE SETTING WILL
SUP04 BE SET TO AT LEAST 1000 FT BELOW GROUND LEVEL OR AT LEAST 90,000 FT AB
SUP05 OVE GROUND LEVEL (-1000 OR 90,000 FT). COORDINATE WITH LOCAL ATC FOR A
M
SUP06 ODE A3 BEACON CODE. STOP BUZZER POC JOHN ADAMS 8033180021 OR
7142625019.