GPS Networking Link Budget Calculator

The following spreadsheet calculates the effective radiated power for a GPS Networking reradiating system as well as the effective signal power at given range in dBm. Enter the components for the strongest repeating path in your system into the section with the red border. NTIA regulations require that the repeated signal be weaker than -140 dBm when measured 100 FT outside of the reradiated structure. Please feel free to reach out to GPS Networking if you need assistance.

Receiving Antenna Gain	Antenna Cable Insertion Loss	System Gain	Nominal Antenna Gain Best Case	Distance to Nearest External Wall (FT)	Signai Power at Nearest External Wall Building	Signal Power at 100' Outside of Nearest External Wall In dBm
38	-4.7	10	4	80	-146.86	-153.90
GPS Carrier Fr	equency MHz		Total System Gain	Range in Miles		ower @ Range in Vatts
	L1: 1575.42 47.3			0.02 2.1E-18		1F_18
Avg Receive	Power dBm Nort	h America				
	-130			Range in Meters 24.38		Power dBm 82.7
Free Space I	loss with Isotropic	Antennas				
-	-64.16			Range in Kilometers	Pow	er (pW)
		-6.11:		0.02		2.69
		oful Links:			Effective Radi	ated Power (pW)
	Get an FCC F	Registration Number		*		
	FCC Experimental Broadcast Form 442				5.37	
	Cable Lo	oss Calculator			***************************************	
	GPS Net	working Store			Effective Radia	ited Power (dBW)
	Email Tim	Waite for help			_1	12.7

Distance to External Wall System Receive	(FT): Antenna	80	ft
Part Number L1GPSA	Gain/Loss 38	(dB)	
Passive Components Part Number	(Cause Los Gain/Loss		
Amplified Components Part Number HNRRKIT	s (Cause Ga Gain/Loss 10		

	Cable R	line		
Cable Type	Loss Per 100 Feet (LMR400 =	Length of Cable	U O	Cable Losses
LMR-400	-6	78.4	ft	-4.70
			ft	0.00

Deposition	Antonno	ft
Repeating A	Antennas	ft
Part Number	Gain/Loss (dB)	ft
L1GRRKPA	4	ft

System Diagram

