

PFD Analysis For SC1 S Band Downlink

In connection with application 0409-EX-CN-2024, FCC has requested the following Power Flux Density (PFD) analysis for the S Band downlink of the spacecraft.

PFD Analysis Method:

PFD (dBW/m²-4kHz) is a function of:

EIRP: Effective, or Equivalent, Isotropically Radiated Power. The center beam equivalent power from the spacecraft antenna, in dBW.

Bandwidth Spreading: The spectrum over which the power of the signal is distributed. This is a function of the telemetry bit rate, the coding rate and the modulation. Hz, which collectively determine symbol rate. The bandwidth is used is 200 kHz, which is the required bandwidth.

Reference Bandwidth: This is set by the Applicable Standard at 4 kHz.

Slant Distance to Earth: this is calculated based on the (minimum) altitude of the satellite, and the elevation angle relative to the horizon at the point where the center beam lands on the Earth Surface.

Applicable Standard:

Radio Regulations, edition of 2016 Vol. 1: Articles, in Table 21-4 (Rev. WRC-15), in the row for 2200 to 2300 MHz, shows emission limits, expressed in units of dBW/m²-4kHz.

TABLE 21-4 (Rev.WRC-15)

Frequency band	Service*	Limit in dB(W/m ²) for angles of arrival (δ) above the horizontal plane			Reference bandwidth	
		0°-5°	5°-25°	25°-90°		
1 670-1 700 MHz	Earth exploration-satellite Meteorological-satellite	-133 (value based on sharing with meteorological aids service)			1.5 MHz	
1 518-1 525 MHz (Applicable to the territory of the United States in Region 2 between the longitudes 71° W and 125° W)	Mobile-satellite (space-to-Earth)	0° ≤ δ ≤ 4°	4° < δ ≤ 20°	20° < δ ≤ 60°	60° < δ ≤ 90°	4 kHz
		-181.0	-193.0 + 20 log δ	-213.3 + 35.6 log δ	-150.0	
1 518-1 525 MHz (Applicable to all other territory of the United States in Region 2)	Mobile-satellite (space-to-Earth)	0° ≤ δ ≤ 43.4°	43.4° < δ ≤ 60°		60° < δ ≤ 90°	4 kHz
		-155.0	-213.3 + 35.6 log δ		-150.0	
1 525-1 530 MHz ⁷ (Region 1, Region 3) 1 670-1 690 MHz ¹² 1 690-1 700 MHz (Nos. 5.381 and 5.382) 1 700-1 710 MHz 2 025-2 110 MHz 2 200-2 300 MHz	Meteorological-satellite (space-to-Earth) Space research (space-to-Earth) Space operation (space-to-space) Space operation (space-to-Earth) Space operation (space-to-space) Earth exploration-satellite (space-to-Earth) Earth exploration-satellite (space-to-space)	0°-5°	5°-25°	25°-90°	4 kHz	
		-154 ⁹	-154 + 0.5(δ - 5) ⁹		-144 ⁹	

To determine conformance, the calculated PFD is compared to the ITU PFD limit. It must be less than this limit, to be in conformance.

PFD Calculation Results:

Tables 1 and 2 show the calculated PFD at 5 degrees and at 90 degrees, and shows that in each case, the calculated PFD is lower than or equal to the ITU PFD limit.

Conclusion:

The SC-1 mission will conform to the ITU PFD limit.

Summary of Calculation

Table 1 PFD Calculation at 5 Degrees Elevation

Parameter	Value
Tx Power, dBW	-7.00
Connector Loss, dBi	2.00
Gain, dB	7.00
EIRP, dBW	-2
Bandwidth, Hz	200,000
Bandwidth, dBHz	53
Reference Bandwidth, Hz	4000
Reference Bandwidth, dbHz	36
EIRP Power Flux Density, dBW/4kHz	-19
Slant distance to Earth surface at minimum operating elevation, km	2083
Beam Spreading Loss to Earth Surface, dB	137.4
Power Flux Density, at Earth Surface, dBW/m ² -4kHz	-156.4
PFD Limit, 5 degree elevation, From RR Article 21.16, Table 21-4, dBW/m ² -4kHz	-154
Margin, dBW/m ² -4kHz	2.4

Table 2 PFD Calculation at 90 Degrees Elevation

Parameter	Value
Tx Power, dBW	-7
Connector Loss, dBi	2.00
Gain, dB	7.00
EIRP, dBW	-2
Bandwidth, Hz	200,000
Bandwidth, dBHz	53
Reference Bandwidth, Hz	4000
Reference Bandwidth, dbHz	36
EIRP Power Flux Density, dBW/4kHz	-19
Distance to Nadir Point, Minimum, km	502
Beam Spreading Loss to Earth Surface, dB	125
Atmospheric Attenuation Loss at Earth Surface, dB	0.1
Power Flux Density, at Earth Surface, dBW/m ² -4kHz	-144
PFD Limit, 90 degree elevation, From RR Article 21.16, Table 21-4, dBW/m ² -4kHz	-144
Margin, dBW/m ² -4kHz	0