

Validation Report for 1 created on 17/01/2025 - start time: 08:30:17 - duration: 0min. 4sec. by user DAVEM using version: 10.0.0.64

E:\MITRE\M-SEL ITU Filing Update - V10 - RF_Fix\CRIM-SEL_v10_CR_RevB.mdb

Satellite Name: M-SEL - Adm.:USA - Orb. Pos.: NGSO - Station Type: N - Notification Reason: Coordination

VALIDATION RESULT: 8 Errors Fatal Errors:3 Warnings:5

Beam	E/R	Grp Id	Table	Field	Value	Row	Valerr	Rule	F/W	Ap4 Ref	Error Message
FLTX	E	11	e_as_stn	bmwidth	7	1	695	4	W	C.10.d.4	Value outside computed allowable range (20.05 - 25.53)
FLTX	E	12	e_as_stn	bmwidth	7	1	695	4	W	C.10.d.4	Value outside computed allowable range (20.05 - 25.53)
FSTX2	E	14	e_as_stn	bmwidth	4.3	1	695	4	W	C.10.d.4	Value outside computed allowable range (9.49 - 12.08)
FLTX	E	11	grp	op_agcy	999		605	3	F	A.3.a	Value = 999 ; please either request the Bureau to allocate an operating agency symbol first, or enter 999 and provide the details of the operating agency or company in an attachment
FLTX	E	12	grp	op_agcy	999		605	3	F	A.3.a	Value = 999 ; please either request the Bureau to allocate an operating agency symbol first, or enter 999 and provide the details of the operating agency or company in an attachment
FSTX2	E	14	grp	op_agcy	999		605	3	F	A.3.a	Value = 999 ; please either request the Bureau to allocate an operating agency symbol first, or enter 999 and provide the details of the operating agency or company in an attachment
FLTX	E		s_beam	gain	7.4		504	3	W	B.3.a.1	For repositionable beam, value < 24.2
FSTX2	E		s_beam	gain	11.1		504	3	W	B.3.a.1	For repositionable beam, value < 24.2