
 ACCESS SERVICE

CHECK SHEET (Cont'd)

Title Page 1 and Pages 1 to 16-16 inclusive of this tariff, Including Supplement No. 1, are effective as of the date shown. Original and revised pages, as named below are in effect on the date indicated.

<u>Page</u>	<u>Number of Revision Except As Indicated</u>	<u>Page</u>	<u>Number of Revision Except As Indicated</u>	<u>Page</u>	<u>Number of Revision Except As Indicated</u>
Title 1	Original	1-1	Original	2-27	Original
				2-28	Original
1	11th *	2-1	Original	2-29	Original
2	Original	2-2	Original	2-30	Original
3	Original	2-3	Original	2-31	Original
4	9th	2-4	Original	2-32	Original
5	Original	2-5	Original	2-33	Original
		2-6	Original	2-34	Original
6	Original	2-7	Original	2-35	Original
7	1st	2-8	Original	2-36	Original
8	Original	2-9	Original	2-37	Original
9	Original	2-10	Original	2-38	Original
10	Original	2-10.1	Original	2-39	Original
11	Original	2-10.2	Original	2-40	Original
12	Original	2-10.3	Original	2-41	Original
13	Original	2-10.4	Original	2-42	Original
14	Original	2-11	Original	2-43	1st *
15	Original	2-12	Original	2-43.1	Original *
16	Original	2-13	Original	2-44	2nd *
17	Original	2-14	Original		
18	Original	2-15	Original	3-1	Original
19	Original	2-16	Original	3-2	Original
20	Original	2-17	Original	3-3	Original
21	Original	2-18	Original	3-4	Original
22	Original	2-19	Original	3-5	Original
		2-20	Original	3-6	Original
		2-21	Original	3-7	Original
		2-22	Original		
		2-23	Original		
		2-24	Original		
		2-25	Original		
		2-26	Original		

*New or Revised Page

ACCESS SERVICE

2. General Regulations (Cont'd)

2.6 Definitions (Cont'd)

Throughput Class

The attainable data rate (bits per second) on packet switched data calls.

Toll VoIP-PSTN Traffic

The term "Toll VoIP-PSTN Traffic" denotes a customer's interexchange voice traffic exchanged with the Telephone Company in Time Division Multiplexing format over Public Switched Telephone Network (PSTN) facilities, which originates and/or terminates in Internet Protocol (IP) format. "Toll VoIP-PSTN Traffic" originates and/or terminates in IP format when it originates from and/or terminates to an end user customer of a service that requires IP-compatible customer premises equipment.

(N)(X)

(N)(X)

(X)(Y)

(X)(Y)

- (X) Issued under authority of Special Permission No. 11-021.
- (Y) Material omitted from this page now appears on Original Page 2-43.1.

ACCESS SERVICE

2. General Regulations (Cont'd)

2.6 Definitions (Cont'd)

Transmission Measuring (105 Type) Test Line/Responder

(M)(X)

The term "Transmission Measuring (105 Type) Test Line/Responder" denotes an arrangement in an end office which provides far-end access to a responder and permits two-way loss and noise measurements to be made on trunks from a near end office.

Trunk

The term "Trunk" denotes a communications path connecting two switching systems in a network, used in the establishment of an end-to-end connection.

Trunk Group

The term "Trunk Group" denotes set of trunks which are traffic engineered as a unit for the establishment of connections between switching systems in which all of the communications paths are interchangeable.

Trunk Side Connection

The term "Trunk Side Connection" denotes the connection of a transmission path to the trunk side of a local exchange switching system.

Two-Wire to Four-Wire Conversion

The term "Two-wire to Four-Wire Conversion" denotes an arrangement which converts a four-wire transmission path to a two-wire transmission path to allow a four-wire facility to terminate in a two-wire entity such as a central office switch trunk circuit or switching system.

Unbundled Network Elements (UNEs)

The term "Unbundled Network Elements" denotes the physical facilities of the network, including the associated features, functions and capabilities, that are capable of being used in the provision of a telecommunications service, made available pursuant to Section 251 of the Telecommunications Act of 1996.

(M)(X)

(M) Material on this page formerly appeared on Original Page 2-43.
(X) Issued under authority of Special Permission No. 11-021.

ACCESS SERVICE

2. General Regulations (Cont'd)

2.6 Definitions (Cont'd)

V&H Coordinates Method

The term "V&H Coordinates Method" denotes a method of computing airline miles between two points by utilizing an established formula which is based on the vertical (V) and horizontal (H) coordinates of the two points.

Virtual Circuit

A communications connection that allows transmission of sequenced data packets through the network. The connection is made up of Logical Channels at the originating and terminating ends of the call as well as intra-network facilities. Transmission bandwidth is only allocated when packets are actually being transmitted.

(D)(X)
| |
| |
(D)(X)

WATS Serving Office

The term "WATS Serving Office" denotes a Telephone Company designated serving wire center where switching, screening and/or recording functions are performed in connection with Special Access Service used in connection with Switched Access Service.

Window Size

The number of outgoing packets that may be sent before confirmation is received indicating that the previous packets have been successfully received.

Wire Center

The term "Wire Center" denotes a building in which one or more central offices, used for the provision of Telephone Exchange Services, are located.

X.25 Packet Mode Protocol

A synchronous network interface protocol as outlined by the CCITT for transmission within a packet switched network (intra-network).

X.75 Packet Mode Protocol

A synchronous network interface protocol as outlined by the CCITT for transmission between packet switching networks (inter-network).

(X) Issued under authority of Special Permission No. 11-021.